

Mikrotik Clientes

/export terse

```
/interface bridge add admin-mac=1A:B0:06:02:XX:30 auto-mac=no name=lo10
/interface ethernet set [ find default-name=ether4 ] disabled=yes
/routing ospf instance set [ find default=yes ] router-id=102.XX.0.252
/routing ospf-v3 instance set [ find default=yes ] router-id=102.XX.0.252
/user group add name=tecnico
policy=ssh,ftp,reboot,read,write,policy,!local,!telnet,!test,!winbox,!passw
ord,!web,!sniff,!sensitive,!api,!romon,!dude,!tikapp
/ip address add address=102.XX.0.2/30 interface=ether1 network=102.XX.0.0
/ip address add address=102.XX.2.1/23 interface=ether2 network=102.XX.2.0
/ip address add address=102.XX.1.1/24 interface=ether3 network=102.XX.1.0
/ip address add address=102.XX.0.252 comment=ROUTER-ID interface=lo10
network=102.XX.0.252
/ip ssh set strong-crypto=yes
/ipv6 address add address=4d0c:abXX:0:1::2/126 advertise=no
interface=ether1
/ipv6 address add address=4d0c:abXX:c000::1/40 advertise=no
interface=ether2
/ipv6 address add address=4d0c:abXX:4000::1/40 advertise=no
interface=ether3
/ipv6 address add address=4d0c:abXX::252/128 advertise=no interface=lo10
/routing ospf network add area=backbone network=102.XX.0.0/30
/routing ospf network add area=backbone network=102.XX.0.252/32
/routing ospf-v3 interface add area=backbone interface=ether1
/routing ospf-v3 interface add area=backbone interface=lo10 passive=yes
/system identity set name=mkt_clientesXX
```

Mikrotik Borda

/export terse

```
/interface bridge add admin-mac=1A:B0:06:01:XX:30 auto-mac=no name=lo10
/interface ethernet set [ find default-name=ether4 ] disabled=yes
/routing ospf instance set [ find default=yes ] router-id=102.XX.0.255
/routing ospf-v3 instance set [ find default=yes ] router-id=102.XX.0.255
/ip address add address=102.XX.0.1/30 interface=ether1 network=102.XX.0.0
/ip address add address=102.XX.0.255 comment=ROUTER-ID interface=lo10
network=102.XX.0.255
/ipv6 address add address=4d0c:abXX:0:1::1/126 advertise=no
interface=ether1
/ipv6 address add address=4d0c:abXX::255/128 advertise=no interface=lo10
/routing ospf network add area=backbone network=102.XX.0.0/30
/routing ospf network add area=backbone network=102.XX.0.255/32
/routing ospf-v3 interface add area=backbone interface=ether1
/routing ospf-v3 interface add area=backbone interface=lo10 passive=yes
/system identity set name=mkt_bordaXX
```